

5MP color in near-total darkness vandal ball turret IP camera DWC-MVA5WiAT / DWC-MPVA5WiAT







Specifications

IMAGE	
Image sensor	5MP 1/2.8" CMOS
Total pixels	2592 (H) X 1944 (V)
	0.08 lux (color)
Minimum scene illumination	0.0 lux (B/W)
LENS	
	0.7.17 Emme El 4
Focal length	2.7-13.5mm, F1.4
Lens type	Vari-focal p-iris lens with motorized zoom and auto-focus
HFOV/VFOV	31° ~ 85°/ 24°~62°
IR distance	100ft range
Optical zoom / digital zoom	x5 optical zoom
OPERATIONAL	
Intelligent Video Analytics	IVA: intrusion, line crossing, counting line, loitering, enter, exi tamper (DWC-MVA5WiAT) IVA+: object removed, tailgating, direction, stopped, appea disappear, object left, logical rules (DWC-MPVA5WiAT)
Shutter mode	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/15 ~ 1/32000
Slow shutter	1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10
Auto gain control	Auto
Day and night	Auto, day (color), night (B/W)
3D Digital noise reduction	Smart DNR™ 3D-DNR
Wide Dynamic Range (WDR)	True WDR, 120dB
Privacy zone	16 programmable privacy masks
Backlight compensation (BLC)	Yes
Mirror and flip	
Alarm notifications	Notifications via e-mail and FTP server recording
NETWORK	
LAN	RJ45 (10/100Base-T)
Video Compression type	H.265, H.264, MJPEG
Resolution	H.265: 2592x1944, 2304x1296, 2.1MP/1080p, 720p, VGA, D1, CIF H.264: 2592x1944, 2304x1296, 2.1MP/1080p, 720p, VGA, D1, CIF MJPEG: 2.1MP/1080p, 720p, 800x600, VGA, 768x432, D1, CIF
Frame rate	Up to 30fps at all resolutions
Video bitrate	H.265 / H.264: 32Kbps - 14Mbps MJPEG: 1Mbps - 40Mbps
Bitrate control	H.265 dual-stream or simultaneous H.265 / H.264 / MJPEG
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4, IPv6
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPVI/v2/v3 (MIB-2), ONVIF
Security	HTTPS (TLS), IP filtering, 802.1x, digest authentication (ID/PW)
ONVIF conformance	Yes
Web viewer	OS: Windows®, Mac® OS, Linux® Browser: IE®, Google Chrome®, Mozilla Firefox®, Safari® NOTE: Chrome browser is recommended for IVA configuration
Video management software	DW Spectrum* IPVMS
ENVIRONMENTAL	
Operating temperature	-4°F ~ 122°F (-20°C ~ 50°C)
Operating humidity	10-90% (non-condensing)
IP rating	IP67-rated
IK rating	IK10 impact-resistant
Other certifications	UL listed, CE, FCC, RoHS
ELECTRICAL	
Power requirement	DC 12V, PoE IEEE 802.3af Class3. (Adapter not included)
Power consumption	DCI2V: max 7.1W PoE: max 8.5W
MECHANICAL	
Material	Aluminum vandal ball turret housing
Dimensions	4.92" x 4.8" (125 x 122 mm)
Weight	1.87lbs (0.85kg)
Warranty	5 year warranty

Summary

This MEGApix[®] IVA[™] IP camera is NDAA compliant and provides 5MP resolution at real-time 30fps with a powerful engine to detect and classify people and vehicles in real-time and IVA+ license for advanced Video Content Analysis detection capabilities. This camera features Star-Light Plus™ color in near-total darkness technology, a 2.7~13.5mm vari-focal auto-focus lens with motorized zoom and weather-resistant vandal ball turret housing that eliminates IR reflections and offer easy angle adjustment for optimal image quality.

Features

- 5MP sensor at real-time 30fps
- Star-Light Plus[™] color in near-total darkness technology
- · Vari-focal p-iris lens with motorized zoom and autofocus for complete remote lens control and focused image any time
- True Wide Dynamic Range (WDR) for clear images in challenging light
- · Simultaneous streaming and multiple codec options for smart bandwidth management
- 100' Smart IR[™] with intelligent camera sync for clear B/W images with no need for external light
- Smart DNR™ 3D digital noise reduction reduces noise and ghosting for motion in low-light environments.
- Privacy zones cover sensitive areas in the camera's field of view.
- · Web server built-in for easy camera management from any browser
- PoE and DC12V for single cable simplified installation
- NDAA compliant for federal and government projects
- IP67- and IK10-rated camera housing built to last
- 5 year warranty

Accessories (Optional)



DWC-PMB-WL-W Pole mount







866.446.3595



Οηνιέ

DWC-VACM Ceiling mount bracket

DWC-VAJUNC Junction box

DWC-VAWM

Wall mount bracket

Copyright © DW. All rights reserved. Specifications and pricing subject to change without notice

t for Users.

www.digital-watchdog.com

