

IVA Inside

STAR-LIGHT PLUS™
Color in Darkness Technology

H.265 H.264/MJPEG **30fps**

2.8/4.0/6.0 mm FIXED LENS OPTIONS

NDAA COMPLIANT PRODUCTS

2.1MP Resolution
Intelligent Video Analytics
Star-Light Plus™
2.8, 4.0, 6.0mm Fixed Lens Options
True WDR
5 YEAR Warranty

Summary

This MEGApix® IVA™ IP camera is your gateway to powerful video analytics features. It is NDAA compliant and provides 2.1MP/1080p resolution at real-time 30fps. The MEGApix IVA cameras have a powerful engine to detect and classify people and vehicles in real-time. IVA+ upgrade offers advanced Video Content Analysis detection capabilities. This camera includes 2.8, 4.0 and 6.0mm fixed lens options, simultaneous H.265/H.264/MJPEG codec support and Star-Light Plus™ color in near-total darkness technology for quality video in any lighting condition, all in an IP67-rated, IK-10 impact resistant ultra low-profile vandal dome housing. All MEGApix® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 2.1MP/1080p 1/2.8" image sensor at real-time 30fps
- Star-Light Plus™ color in near-total darkness technology
- Intelligent Video Analytics (IVA)
- Extended Intelligent Video Analytics (IVA+ required)
- Seamless integration and control of IVA rules with DW Spectrum® IPVMS
- Reduce false alarms
- Increase your recording storage with logic rules and smart recording
- 2.8mm fixed lens (DWC-MV72Wi28TW)
- 4.0mm fixed lens (DWC-MV72Wi4TW)
- 6.0mm fixed lens (DWC-MV72Wi6TW)
- True Wide Dynamic Range (WDR)
- Triple codecs (H.265, H.264, MJPEG) with simultaneous streaming
- 80' Smart IR™ with intelligent camera sync
- Ultra low-profile vandal dome camera
- Smart DNR™ 3D digital noise reduction
- True day/night mechanical IR cut filter
- Programmable privacy zones
- Auto gain control (AGC)
- Auto white balance (AWB)
- Motion detection
- Micro SD/SDHC/SDXC class 10 card slot (card not included)
- PoE class 2 and DC12V
- UL listed
- NDAA compliant
- IP67 dust-tight and waterproof to 3 feet
- IK 10-rated impact-resistant
- 5 year warranty




Accessories (optional)



Dimensions

Unit: Inch (mm)



Specifications



IMAGE	
Image sensor	2.1MP/1080p 1/2.8" CMOS
Total pixels	1945 (H) X 1109 (V)
Minimum scene illumination	0.05 lux (color) (DWC-MV72Wi28TW) 0.09 lux (color) (DWC-MV72Wi4TW) 0.05 lux (color) (DWC-MV72Wi6TW) 0.0 lux (B/W)
LENS	
Focal length	2.8mm, F2.0 (DWC-MV72Wi28TW) 4.0mm, F2.6 (DWC-MV72Wi4TW) 6.0mm, F2.0 (DWC-MV72Wi6TW)
Lens type	Fixed lens
HFOV / VFOV	111° / 62° (DWC-MV72Wi28TW) 86° / 46° (DWC-MV72Wi4TW) 55° / 30° (DWC-MV72Wi6TW)
IR distance	80ft range
OPERATIONAL	
Intelligent Video Analytics	IVA: intrusion, line crossing, counting line, loitering, enter, exit, tamper IVA+: object removed, tailgating, direction, stopped, appear, disappear, object left, logical rules
Shutter mode	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/15 - 1/32000
Slow shutter	1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10
Auto gain control	Auto
Day and night	Auto, day (color), night (B/W)
Smart DNR™ 3D Digital Noise Reduction	3D-DNR
Wide Dynamic Range (WDR) dB	True WDR, 120dB
Privacy zone	16 programmable privacy masks
Mirror and flip	Yes
Alarm notifications	Notifications via e-mail notifications, FTP and SD card recording
Memory slot	Micro SD / SDHC / SDXC (card not included)
NETWORK	
LAN	RJ45 (10/100Base-T)
Video compression type	H.265, H.264, MJPEG
Resolution	H.265: 2.1MP/1080p, 720p, VGA, D1, CIF H.264: 2.1MP/1080p, 720p, VGA, D1, CIF MJPEG: 1280x720, 800x600, VGA, 768x432, D1, CIF
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps - 10Mbps, multi-rate for preview and recording
Bitrate control	Multi streaming CBR/VBR at H.264, H.265 (controllable frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4, IPv6
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3 (MIB-2), ONVIF
Security	HTTPS (TLS), IP filtering, 802.1x, digest authentication (ID/PW)
ONVIF conformance	Yes
Web viewer	OS: Windows®, Mac® OS, Linux® Browser: Internet Explorer®, Google Chrome®, Mozilla Firefox®, Safari® NOTE: Chrome browser is recommended for IVA configuration
Video management software	DW Spectrum® IPVMS
ENVIRONMENTAL	
Operating temperature	-4°F - 122°F (-20°C - 50°C)
Operating humidity	10-90% (non-condensing)
IP and IK rating	IP67-rated, IK10 impact-resistant
Other certifications	UL listed, CE, FCC, RoHS
ELECTRICAL	
Power requirement	DC 12V, PoE IEEE 802.3af Class2. (Adapter not included)
Power consumption	DC12V: max 3.7W, PoE: max 5.5W
MECHANICAL	
Material	Aluminum vandal housing, polycarbonate dome
Dimensions	4.13" x 2.4" (105 x 61mm)
Weight	0.79lbs (0.36kg)
Warranty	5 year warranty