

5MP vandal fisheye edge IP camera

DWC-PVF5M1TIRWC5, DWC-PVF5M1TIRWC1T




















Dimensions

unit: inch (mm)

OPERATIONAL Shutter mode

Shutter speed





Summary

MEGApix® CaaS™ all-in-one series of IP cameras combine the cameras with the ease and power of DW Spectrum® IPVMS and onboard storage up to 1TB. DW Spectrum IPVMS server is pre-installed and licensed. No additional server hardware is required.

The 5MP fisheye camera offers 360° Smart IR™ and a 1.55mm fisheye lens in an IP66-rated discrete vandal housing. Combine the CaaS™ solution with the Blackjack® NAS device for long-term storage needs.

-eatures

- All-in-one cameras, no server required
- 5MP 1/1.8" image sensor at real-time 30fps
- 1.5mm fisheye lens
- Built-in 512GB and 1TB storage options for up to 60 days retained video*
- Support 360° hemispheric fisheye view and 360°, 180° and 90° panoramic views
- Edge-to-edge image clarity
- Easily to deploy with pre-loaded DW Spectrum IPVMS for out-of-the-box operation
- 24/7 access to live and recorded video feed
- Automatic installation and licensing with first power on
- Connect up to 30 MEGApix CaaS edge cameras
- Dual recording option with Blackjack NAS appliance
- Dual codecs (H.264, MJPEG) with simultaneous dual-stream
- 55' Smart IR™ with intelligent camera sync
- Smart DNR™ 3D digital noise reduction
- True day/night with mechanical IR cut filter
- Programmable privacy zones
- Auto gain control (AGC)
- Backlight compensation (BLC)
- Auto white balance (AWB)
- Motion detection
- Web server built-in
- PoE class 3 and DC12V
- · Waterproof cabling
- ONVIF conformant, profile S
- NDAA compliant
- IP66 environmental-rated dust-tight and water-resistant
- 5 year warranty



Accessories (Optional)



DWC-VFCMW Wall mount bracket



DWC-VFWMW Junction box



DWC-VFJUNCW Ceiling mount bracket





DWC-PMB-WLW Pole mount



DWC-WMJUNCW Junction box for wall mount brackets

Specifications

Image sensor	5MP 1/1.8" CMOS sensor
Total pixels	3096 (H) X 2080 (V)
Minimum scene illumination	0.39 lux (color)
	0 lux (B/W)
Video output	Local video output CVBS 1.0V p-p (75Ω)], 4:3 aspect ratio
Resolution	5MP (2592x1944)
LENS	
Focal length	1.55mm, F2.5
Lens type	Fisheye lens
Field of view (FoV)	360°
IR distance	55ft range

Slow snutter	1~1/5,1/7.5, 1/10
Auto gain control	Auto
Day and night	Auto, day (Color), night (B/W)
Smart DNR™ 3D digital noise reduction	0-11
	4.6

1/30 - 1/32000

Auto, manual, anti-flicker, slow shutter

4 Programmable privacy masks Notifications via e-mail, FTP server or SD card recording Privacy zone Alarm notifications NETWORK 10/100 Based-T, RJ-45 connector Video compression type H.264, MJPEG

2592 X 1944 @ 30fps, 640X480 @ 30fps, 320X240 @ 30fps Resolution Frame rate Up to 30fps at all resolutions Video bitrate 100Kbps - 10mbps, multi-rate for preview and recording Multi streaming CBR/VBR at H.264 (Controllable frame rate and bandwidth) Bitrate control

Streaming capability Dual-stream at different rates and resolutions IPv4 Zero config (Auto IP), ONVIF, TCP/IP, UDP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, Protocol ICMP, SNMPv1/v2c/v3 (MIB-2)

HTTPS (TLS), IP filtering, 802.1x, digest authentication (ID/PW) Maximum user access Onvif conformance 5 users Yes

OS: Windows*, Mac* OS, Linux* Browser: Internet Explorer*, Google Chrome*, Mozilla Firefox*, Safari* Video management software DW Spectrum® IPVMS Number of DW Spectrum® IPVMS licenses included 1 DW Spectrum® license

DWC-PVF5M1TIRWC1T: 1TB local memory for recording DWC-PVF5M1TIRWC5: 512GB local memory for recording Up to 30 MEGApix® CaaS™ cameras in the

Max. Number of CaaS™ cameras in the same network/system same network/system ENVIRONMENTAL -4°F ~ 122°F (-20°C ~ 50°C) Operating temperature

Operating humidity IP rating Less than 90% (Non-condensing) IP66-rated FCC, CE, ROHS, UL listed Other certifications Electrical

DC12V, PoE (IEEE 802.3af Class 3). Adaptor not included. Power requirement

LED on: 6.5W LED off: 3.6W Power consumption MECHANICAL Aluminum vandal fisheye housing, polycarbonate dome $4.9" \times 1.88" (125 \times 48 \text{mm})$ Material Dimensions Weight 1.1 lbs (0.5kg)

NOTE:

1. External ONVIF devices cannot be added
2. IVA/IVA+ is not available on this model
3. Plugins from external devices cannot be added



Increase sales and profitability. Sign up and become a DW Channel Partner today!









: sales@digital-watchdog.com



Warranty

(: www.digital-watchdog.com