






Dimensions



Specifications



Summary

These MEGApix® IP cameras are NDAA compliant and deliver crystal-clear images at 4MP resolution and real-time 30fps. The bullet camera features a 2.8-12mm vari-focal lens in an IP67-rated, IK10 impact-resistant housing. Added intelligence includes line crossing, perimeter intrusion and video tampering detection. All MEGApix cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 4MP 1/3" image sensor at real-time 30fps
- Vari-focal lens with motorized zoom and autofocus for complete remote lens control and focused image any time
- True Wide Dynamic Range (WDR) for clear images in challenging light
- Simultaneous streaming and multiple codec options for smart bandwidth management
- 164' Smart IR™ with intelligent camera sync for clear B/W images with no need for external light
- Line crossing video analytics
- Perimeter intrusion video analytics
- Video tampering with scene-change, video-blur and abnormal color detection video analytics
- Smart DNR™ 3D digital noise reduction reduces noise and ghosting for motion in low-light environments.
- · Privacy zones cover sensitive areas in the camera's field of view.
- Backlight compensation (BLC)
- Built-in microphone and audio input for direct communication between the monitoring station and the camera's location
- Local SD card slot for local recording in case of network loss
- Web server built-in for easy camera management from any browser
- PoE and DC12V for single cable simplified installation
- NDAA compliant for federal and government projects
- IP67-rated camera housing built to last
- 5 year warranty

Mounting accessories (Optional)



Image sensor 4MP 1/3" CMOS 2560 x 1440 Total pixels 0.005 lux (color) Minimum scene illumination 0.0 lux (B/W) S/N ratio 50dB LENS Focal length 2.8 ~ 12mm, F1.4 Lens type Vari-focal lens with motorized zoom and auto-focus Horizontal Field of View 92°~31° 48° ~ 17.2° Vertical Field of View IR distance 164ft range 1/0 Audio in / out 1 audio input and 1 microphone built-in Audio compression G.711A / U **OPERATIONAL** Shutter mode Auto, manual Shutter speed 1/2s ~ 1/100000s Auto gain control Auto Auto, day (color), night (B/W), schedule Smart DNR™ 3D digital noise reduction Day / night 3D DNR Wide dynamic range (WDR) True WD, 120dB Privacy zone 8 programmable privacy masks Line crossing, perimeter intrusion, video tampering Video analytics detection (scene change, video blur, abnormal color) Backlight compensation (BLC) Yes Mirror and flip Notifications via email or FTP server Alarm notifications Memory slot Micro SD, SDHC, SDXC up to 256GB (card not Included) **NETWORK** LAN 802.3 compliance 10/100 LAN Video compression type H.265, H.264, MJPEG 4MP, 3MP, 2.1MP/1080P, 720P, D1, 480x240, CIF Resolution (60Hz: 1 ~ 30fps; 50Hz: 1~25fps) Frame rate Up to 30fps at all resolutions Video bitrate 64 Kbps ~ 8 Mbps Multi-streaming CBR/VBR at H.264/ H.265 Bitrate control (controllable frame rate and bandwidth) Dual-stream at different rates and resolutions Streaming capability Maximum three (3) connections/streams at a time IPv4, IPv6 IK rating IK10-rated housing, IK03-rated glass cover UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, ICMP, Protocol IGMP, PPPoE, DDNS, SMTP, FTP, SNMP,HTTP, 802.1x, UPnP, HTTPs, QoS Security IP filtering, MAC filtering, authentication (ID/PW), SSL/TSL ONVIF conformance OS: Windows®, Mac® OS, Linux® Web viewer Browser: MS Edge, IE, Chrome, Firefox Video management software DW Spectrum® IPVMS **ENVIRONMENTAL** Operating temperature -22°F ~ 140°F (-30°C ~ 60°C) 0-95% RH (non-condensing) Operating humidity IP rating IP67-rated Other certifications FCC, CE, ROHS, ONVIF, NDAA ELECTRICAL Power requirement DC 12V, PoE (Adapter not included) Power consumption <8\/\ **MECHANICAL** Material Metal bullet housing Dimensions 8.69" x 3.16" x 2.77" (220.8 x 80.5 x70.6 mm) Weight 1.52 lb (0.69 kg)













5 year warranty