

















Smart IR"





Warranty

Summary

These MEGApix® IP cameras are NDAA compliant and deliver crystalclear images at 4MP resolution and real-time 30fps. The bullet camera features a 2.8~12mm vari-focal lens in an IP67-rated, IK10 impact-resistant housing. Added intelligence includes line crossing, perimeter intrusion and video tampering detection. All MEGApix cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 4MP 1/3" image sensor at real-time 30fps
- 2.8-12mm vari-focal lens with motorized zoom and auto-focus
- True Wide Dynamic Range (WDR)
- Multiple codecs (H.265, H.264, MJPEG) with simultaneous dualstream
- 164ft range Smart IR
- Line crossing video analytics
- Perimeter intrusion video analytics
- Video tampering with scene-change detection video analytics
- Video tampering with video-blur detection video analytics
- Video tampering with abnormal color detection video analytics
- Smart DNR 3D digital noise reduction
- True day/night with mechanical IR cut filter
- Programmable privacy zones
- Auto gain control (AGC)
- Backlight compensation (BLC)
- Auto white balance (AWB)
- Motion detection
- Audio input and microphone built-in
- Micro SD/SDHC/SDXC class 10 card slot (card not included)
- Web server built-in
- PoE class3 and DC12V
- ONVIF conformant, profile S
- NDAA compliant
- IP67 dust-tight and waterproof to 3 feet
- IK 10-rated impact-resistant
- 5 year warranty




Mounting accessories (Optional)





Increase sales and profitability. Sign up and become a DW Channel Partner today!










Dimensions

Unit: Inch (mm)





Specifications



IMAGE	
Image sensor	4MP 1/3" CMOS
Total pixels	2560 x 1440
	0.005 lux (color)
Minimum scene illumination	0.0 lux (B/W)
S/N ratio	50dB
LENS	10005
Focal length	2.8 ~ 12mm, F1.4
Lens type	Vari-focal lens with motorized zoom and auto-focus
Field of view (FoV)	92°~31°
IR distance	164ft range
1/0	
Audio in / out	1 audio input and 1 microphone built-in
Audio compression	G.711A / U
Event Trigger	Motion alarm/sensor alarm
	Pre: 1~5 sec.
Pre-Post Recording	Post: 1~120 sec.
OPERATIONAL	
Shutter mode	Auto, manual
Shutter speed	1/2s ~ 1/100000s
Auto gain control	Auto
Day / night	Auto, day (color), night (B/W), schedule
Smart DNR™ 3D digital noise	3D DNR
reduction	
Wide dynamic range (WDR)	True WDR low, middle, high
Wide dynamic range (WDR) dB	
Privacy zone	8 programmable privacy masks
Video analytics	Line crossing, perimeter intrusion, video tampering detection (scene change, video blur, abnormal color detection)
Backlight compensation (BLC)	Yes
Mirror and flip	Yes
Alarm notifications	Notifications via email or FTP server
	Micro SD / SDHC / SDXC card up to 256GB
Memory slot	(card not Included)
NETWORK	
LAN	802.3 compliance 10/100 LAN
Video compression type	H.265, H.264, MJPEG
Resolution	4MP, 3MP,2.1MP/1080P, 720P, D1, 480x240, CIF
	(60Hz: 1 ~ 30fps; 50Hz: 1~25fps)
Frame rate	Up to 30fps at all resolutions
Video bitrate	64 Kbps ~ 8 Mbps
Bitrate control	Multi-streaming CBR/VBR at H.264/ H.265 (controllable frame rate and bandwidth)
	Dual-stream at different rates and resolutions
Streaming capability	Maximum three (3) connections/streams at a time
IP	IPv4, IPv6
	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP,
Protocol	ICMP, IGMP, PPPoE, DDNS, SMTP, FTP, SNMP,HTTP,
	802.1x, UPnP, HTTPs, QoS
Security	IP filtering, MAC filtering, authentication (ID/PW), SSL/TSL
ONVIF conformance	Yes
Web viewer	OS: Windows®, Mac® OS, Linux®
	Browser: MS Edge, IE, Chrome, Firefox
Video management software	DW Spectrum* IPVMS
ENVIRONMENTAL	
Operating temperature	-22°F ~ 140°F (-30°C ~ 60°C)
Operating humidity	0-95% RH (non-condensing)
IP rating	IP67-rated
IK rating	IK10 impact-resistant
Other certifications	FCC, CE, ROHS, ONVIF, NDAA
ELECTRICAL	DO 10/ D 5 1555 000 7 (0)
Power requirement	DC 12V, PoE IEEE 802.3af Class 3. (Adapter not included)
Power consumption	<8W
MECHANICAL	1
Material	Metal bullet housing
Dimensions	8.69" x 3.16" x 2.77" (220.8 x 80.5 x70.6 mm)
Weight Warranty	1.52 lb (0.69 kg) 5 year warranty
vvarrant/	
vvariancy	5 year warranty



